## Solving a Relaxed Min-Cost Redundancy Allocation Model using Lagrange Multiplier and Newton's Method

#### Abstract

Redundancy allocation is a valuable technique that system engineers can use to design high level of reliability into complex systems. Broadly however, redundancy allocation problems are NP-hard. The main goal of this paper is to solve a relaxed minimum-cost problem by proving that Newton's method finds the optimal value of the Lagrange multiplier. The paper first establishes lower and upper bounds on the optimal Lagrange multiplier, and then starting from an initial value determined by he the model's parameters, Newton's method finds the optimal value of the Lagrange multiplier. The paper also illustrates the method with two examples and presents a general conclusion.

Keywords: redundancy allocation models, NP-hard redundancy allocation models, discrete optimization problems, Lagrange multipliers, Newton's

1

method

### 1 Introduction

This paper deals with non-linear optimization problems of the form

$$\min \sum_{i=1}^{n} c_i x_i \tag{1}$$

subject to 
$$\prod_{i=1}^{n} (1 - \rho_i^{x_i}) \ge R$$
 and  $x_i > 0, i = 1, ..., n$ .

The size of the model, n, is an integer greater than 1 and the values of the decision variables,  $x_1, x_2, \ldots, x_n$ , are restricted to positive real numbers. The objective coefficients are positive real numbers  $c_1, c_2, \ldots, c_n$ . Since the objective is linear, it can be scaled so that  $\min_{1 \le i \le n} c_i = 1$ . The constraint parameters are real numbers, R, the predetermined system reliability, and  $\rho_i$ ,  $i = 1, 2, 3, \cdots, n$ , the unreliability component at the  $i^{th}$ stage, for which 0 < R < 1 and  $0 < \rho_i < 1$  for  $i = 1, 2, \ldots, n$ .

Model (1) can be solved by the method of Lagrange multipliers. Nmah ([1] and [2]) showed that there is a unique optimal solution  $(x_1^*, x_2^*, \dots, x_n^*)$  of the form

$$x_i^* = \ln(c_i/(c_i + \lambda^* R \ln(\rho_i^{-1}))) / \ln(\rho_i),$$
 (2)

where  $\lambda^*$  is the unique positive root of the equation

$$\prod_{i=1}^{n} \lambda R \ln(\rho_i^{-1}) / (c_i + \lambda R \ln(\rho_i^{-1})) = R.$$
(3)

The classic redundancy allocation model is a discrete optimization model that differs from (1) only in that the values of the decision variables,  $x_i$ , are restricted to positive integers. In the context of redundancy allocation, the optimal values of the decision variables for the discrete optimization model show the levels of redundancy for each subsystm in a series system that will achieve a required level of reliability, while minimizing a competing characteristic, such as cost or weight.

The purpose of this work is to show that Equation (3) can be solved by Newton's method from an initial value determined by the model's parameters. The main result of Section 2 gives upper and lower bounds for the root  $\lambda^*$ . The results of Section 3 show how to approximate  $\lambda^*$  by Newton's method, and Section 4 presents examples and conclusions.

### Review of related works

The desire to improve the reliability of products or complex systems in a competitive market has been of paramount interest to industries (Leon and Cascaval [3]). As Rice et al [4] and Kuo and Wan [5] pointed out, redundancy allocation can be used to improve the reliability of a structure with inadequate reliability. In fact, since the birth of the industrial revolution, manufacturers have been finding ways to build trust in their products. But

it was not until after the Second World War that the scholarly foundations of reliability were developed (Japan Standard Association [6] and Tillman et al [7]).

To meet this desired need, industrial system designers have turned to redundancy allocation techniques (Rice et al [42], Tillman et al [8], and Devi et al [9]). Redundancy allocation is a useful and practical technique that engineering designers use when designing engineering systems that need high levels of system reliability while satisfying limitations on cost, weight, volume, etc.(Rice et al [4]). It is done during the design phase where system designers install additional identical redundant components arranged in parallel. Thus, redundancy allocation models may be viewed as system designs in which system engineers built component redundancies into the system. Both Elsayed [10] and Chern [11] pointed out that, in general, redundancy allocation models are NP-hard.

One of the initial methods for solving optimal redundancy allocation problems was based on the classical Lagrange multiplier method (Ushakov [12]). Li and Zio [13], Devi et al [9] as well as Tillman et al [7], respectively, gave indepth and comprehensive literature reviews of various redundancy allocation models. Both Li et al [13] and Leon et al [14] considered several optimization methods for redundancy allocation in large systems and did an excellent study of series-parallel reliability models. Recently, the use of redundancy allocation models has entered into the space of artificial intelligence Devi et al [9].

# 2 Upper and Lower Bounds on the Optimal Lagrange Multiplier

Constants  $a_1, a_2, \ldots, a_n$  can be computed from the parameters  $c_i, \rho_i$ , and R of Model (1) with the equations

$$a_i = c_i / R \ln(\rho_i^{-1}). \tag{4}$$

These strictly positive constants determine a rational function f defined on  $[0,\infty)$  as

$$f(\lambda) = \prod_{i=1}^{n} \lambda/(a_i + \lambda). \tag{5}$$

When Equation (3) is rewritten in terms of  $a_1, a_2, \ldots, a_n$ , the result is

$$f(\lambda^*) = R. (6)$$

Let  $a_{min}$  and  $a_{max}$  denote the smallest and largest of the constants in Equation (4) and let the constants  $\lambda_{min}$  and  $\lambda_{max}$  be given by the equations

$$\lambda_{min} = a_{min} \frac{R^{1/n}}{1 - R^{1/n}}$$
 and  $\lambda_{max} = a_{max} \frac{R^{1/n}}{1 - R^{1/n}}$ .

**Proposition 1** The optimal Lagrange multiplier  $\lambda^*$  satisfies the inequalities  $\lambda_{min} \leq \lambda^* \leq \lambda_{max}$ .

*Proof.* The function f is strictly increasing on  $[0, \infty)$  and its range is the interval [0, 1). Since 0 < R < 1, Equation (6) has a unique, strictly positive solution. Clearly,  $0 < \lambda_{min} \le \lambda_{max}$  and

$$\left(\frac{\lambda_{min}}{a_{min} + \lambda_{min}}\right)^n = R = \left(\frac{\lambda_{max}}{a_{max} + \lambda_{max}}\right)^n.$$

Since  $f(\lambda) \leq (\lambda/(a_{min} + \lambda))^n$ , it follows that  $f(\lambda_{min}) \leq R$  and  $\lambda_{min} \leq \lambda^*$ . Likewise,  $f(\lambda) \geq (\lambda/(a_{max} + \lambda))^n$ , so  $\lambda_{max} \geq \lambda^*$ .

Corollary 1 Either  $a_{min} = a_{max}$ , in which case  $\lambda^* = \lambda_{min}$  and  $f(\lambda_{min}) = R$ , or  $a_{min} < a_{max}$ , in which case  $\lambda^* > \lambda_{min}$ , and  $f(\lambda_{min}) < R$ .

Proof. If  $a_{min} = a_{max}$ , then the proposition shows that  $\lambda^* = \lambda_{min}$  and so  $f(\lambda_{min}) = R$ . If  $a_{min} < a_{max}$ , then  $f(\lambda) < (\lambda/(a_{min} + \lambda))^n$  on  $(0, \infty)$ . In particular,  $f(\lambda_{min}) < R$ , so  $\lambda^* > \lambda_{min}$ .

Corollary 2 For  $\rho$  and R in (0,1), set  $c_i = 1$  and  $\rho_i = \rho$  for  $1 \le i \le n$ . Then the solution of Model (1) is

$$\lambda^* = R^{1/n} / \ln(\rho^{-1}) R (1 - R^{1/n}),$$

and

$$x_i^* = \ln(1 - R^{1/n}) / \ln(\rho)$$
 for  $1 \le i \le n$ .

*Proof.* For these parameters,  $a_{min} = a_{max} = 1/R \ln(\rho^{-1})$ . Then, the optimal value  $\lambda^*$  is given by the previous proposition and the optimal values of the coordinates  $x_i^*$  are given by Equation (2).

### 3 Using Newton's Method

The purpose of this section is to establish that Newton's method, applied to a transformation of the function f of Equation (5) and initialized with  $\lambda_{min}$ , generates an increasing sequence that converges to the optimal Lagrange multiplier.

**Definition 1** For the constants  $a_1, a_2, \ldots, a_n$ , of Equation (4), the function h is defined on  $(0, \infty)$  as

$$h(\lambda) = \ln(f(\lambda)) - \ln(R) = \sum_{i=1}^{n} \ln(\lambda/(a_i + \lambda)) - \ln(R).$$

**Lemma 1** Let h be as defined on  $(0, \infty)$  in Definition 1. Then  $h^{(k)}(\lambda) = (-1)^{k-1}(k-1)! \sum_{i=1}^{n} \left(\frac{1}{\lambda^{k}} - \frac{1}{(a_{i} + \lambda)^{k}}\right), k = 1, 2, 3, \cdots$ 

*Proof.* The proof follows from the Principle of Mathematical Induction. To begin, let k = 1; then:

$$h'(\lambda) = \frac{d}{d\lambda} \left( \sum_{i=1}^{n} \ln \left( \frac{\lambda}{(a_i + \lambda)} \right) - \ln(R) \right)$$
$$= \sum_{i=1}^{n} \frac{d}{d\lambda} \left( \ln(\lambda) - \ln(a_i + \lambda) \right)$$
$$= \sum_{i=1}^{n} \left( \frac{1}{\lambda} - \frac{1}{a_i + \lambda} \right)$$

Now assume that it is true for k. That is,

$$h^{(k)}(\lambda) = (-1)^{k-1}(k-1)! \sum_{i=1}^{n} \left( \frac{1}{\lambda^k} - \frac{1}{(a_i + \lambda)^k} \right).$$

Then for k + 1, we have  $h^{(k+1)}(\lambda) = \frac{d}{d\lambda}h^{(k)}(\lambda)$ ,

which by the induction hypothesis is equivalent to:

$$h^{(k+1)}(\lambda) = \frac{d}{d\lambda} \left( (-1)^{k-1} (k-1)! \sum_{i=1}^{n} \left( \frac{1}{\lambda^k} - \frac{1}{(a_i + \lambda)^k} \right) \right)$$

$$= (-1)^{k-1} (k-1)! \frac{d}{d\lambda} \left( \sum_{i=1}^{n} \left( \frac{1}{\lambda^k} - \frac{1}{(a_i + \lambda)^k} \right) \right)$$

$$= (-1)^{k-1} (k-1)! (-k) \sum_{i=1}^{n} \left( \frac{1}{\lambda^{k+1}} - \frac{1}{(a_i + \lambda)^{k+1}} \right)$$

$$= (-1)^k k! \sum_{i=1}^{n} \left( \frac{1}{\lambda^{k+1}} - \frac{1}{(a_i + \lambda)^{k+1}} \right) . \blacksquare$$

**Note**: While all we need is  $h \in C^2((0,\infty))$ , it is clear from Lemma 1 that  $h \in C^\infty((0,\infty))$ .

**Lemma 2** The function h is strictly increasing on  $(0, \infty)$  and strictly con-

cave there.

*Proof.* On  $(0, \infty)$ , the derivative, h', is strictly positive and the second derivative, h, is strictly negative. In fact, Lemma 1 with k = 1, 2 yields  $h'(\lambda) = \sum_{i=1}^{n} \left(\frac{1}{\lambda} - \frac{1}{a_i + \lambda}\right)$  and  $h''(\lambda) = -\sum_{i=1}^{n} \left(\frac{1}{\lambda^2} - \frac{1}{(a_i + \lambda)^2}\right)$ .

Corollary 3 The optimal Lagrange multiplier  $\lambda^*$  is the unique zero of the function h.

*Proof.* That  $h(\lambda^*) = 0$  follows from the definition of the function h. This root is unique because h is strictly increasing and its range is  $(-\infty, 0)$ .

**Definition 2** When  $a_{min} < a_{max}$ , the sequence  $\lambda_k$  is generated by the equations  $\lambda_0 = \lambda_{min}$  and  $\lambda_{k+1} = \lambda_k - h(\lambda_k)/h'(\lambda_k)$ .

When  $a_{min} = a_{max}$ , Corollary 1 shows that no iterative method is needed to find the root  $\lambda^*$ . When  $a_{min} < a_{max}$ , the proof of Theorem 1 will show that each term of the sequence  $\{\lambda_k : k > 0\}$  is positive and thus in the domain of the functions h and h'.

The proofs of the next two theorems are adaptations of an argument in Allen & Isaacson [15], where it is attributed to Henrici [16].

**Theorem 1** If  $a_{min} < a_{max}$ , then, for k > 0,  $0 < \lambda_{min} < \lambda_k < \lambda_{k+1} < \lambda^*$ .

Proof. Suppose  $a_{min} < a_{max}$ . Then Corollary 1 shows that  $\lambda_0 < \lambda^*$ , and so  $h(\lambda_0) < 0$ . Furthermore, since  $h'(\lambda_0) > 0$  and  $\lambda_1 = \lambda_0 - h(\lambda_0)/h'(\lambda_0)$ , it follows that  $\lambda_1 > \lambda_0$ .

Next, we need to show that  $\lambda_1 < \lambda^*$ . Since  $\lambda_0 < \lambda^*$ , the Mean Value Theorem implies that  $-h(\lambda_0) = h(\lambda^*) - h(\lambda_0) = h'(c)(\lambda^* - \lambda_0)$  for some  $c \in (\lambda_0, \lambda^*)$ . From Lemma 2, h' is strictly decreasing, so  $h'(c) < h'(\lambda_0)$ . Thus,  $-h(\lambda_0) < h'(\lambda_0)(\lambda^* - \lambda_0)$ , or  $\lambda_1 - \lambda_0 < \lambda^* - \lambda_0$ .

Next, assume that  $\lambda_0 < \lambda_k < \lambda^*$ . As above, it follows that  $\lambda_{k+1} > \lambda_k$ . From the Mean Value Theorem and the fact that h' is decreasing, we have  $-h(\lambda_k) < h'(\lambda_k)(\lambda^* - \lambda_k)$ , or  $\lambda_{k+1} - \lambda_0 < \lambda^* - \lambda_0$ .

As noted by Allen & Isaacson [15] and Henrici [16], the next theorem relies on a result from the theory of real variables which states that a bounded, nondecreasing sequence of real numbers converges to its least upper bound (Lebl [17]).

**Theorem 2** If  $a_{min} < a_{max}$ , then  $\lim_{k \to \infty} \lambda_k = \lambda^*$ .

Proof. Suppose  $a_{min} < a_{max}$ . Then by Theorem 1,  $\{\lambda_k\}$  is a bounded, nondecreasing sequence of real numbers. Thus, it has a limit, say  $\bar{\lambda}$ . From Theorem 1, it also follows that  $0 < \lambda_{min} < \bar{\lambda} \le \lambda^*$  and so  $\bar{\lambda}$  is in the domain of both h and h'. Then since h and h' are continuous and h' is strictly positive on  $(0, \infty)$ , taking limits, as in Henrici [16], on both sides gives  $\bar{\lambda} = \bar{\lambda} - h(\bar{\lambda})/h'(\bar{\lambda})$  or  $h(\bar{\lambda}) = 0$ . By Corollary 3,  $\lambda^*$  is the only zero of h, and so,  $\bar{\lambda} = \lambda^*$ .

### 4 Examples and Conclusions

The main result of this paper is to solve a relaxed minimum-cost redundancy allocation problem by showing that Newton's method finds the value of the optimal Lagrange multiplier.

Elsayed [10] posed a problem with n = 3,  $c_1 = c_2 = c_3 = 1$ , minimum required system reliability, R = 0.82, and component unreliabilities  $\rho_1 = 0.30$ ,  $\rho_2 = 0.25$ , and  $\rho_3 = 0.15$ . Table 1 displays the solution to the Lagrange multiplier problem, using Newton's method.

Table 1 Computing the Optimal Lagrange multiplier

k	$\lambda_k$	$ \lambda_{k+1} - \lambda_k $	k	$\lambda_k$	$ \lambda_{k+1} - \lambda_k $
0	9.399742		3	12.34503257	0.03609972
1	11.665351	2.265609	4	12.34505203	$1.946 \times 10^{-5}$
2	12.30893285	0.64358185			

Now, using  $\lambda^* = 12.34505$  and Equation (2), we calculate the unique optimal solution  $x^*$  to the continuous relaxation model to be

(2.142314, 1.955049, 1.584455) and min  $z = \sum_{i=1}^{n} c_i x_i^* = 5.681819$ . Rounding up z, we get a lower bound of 6 for optimal objective value of discrete model, and rounding up coordinates of the optimal solution to the relaxed model, we get (3, 2, 2) which is feasible for the discrete model, and the objective value of this feasible solution is 7 which is an upper bound for the optimal objective value of the discrete model. **Note**: In general, the feasible

solution obtained by rounding up the coordinates of the optimal solution of the relaxed model is not optimal. Using the reduction procedure in Nmah [18], we get (2, 2, 2) which yiels z = 6, the lower bound for optimal of discrete model, and hence optimal solution for the discrete model.

We observe that Elsayed [10] achieved the same result but by a different method. Next, Rice et al [4] posed a problem with  $n=3, R=0.995, \rho_1=0.1, \rho_2=0.125, \rho_3=0.09, c_1=4, c_2=1, and c_3=3$ . Table 2 displays the results of the Lagrange multiplier problem, using Newton;s method.

Table 2 Computing the Optimal Lagrange multiplier

k	$\lambda_k$	$ \lambda_{k+1} - \lambda_k $	k	$\lambda_k$	$ \lambda_{k+1} - \lambda_k $
0	289.0217848		4	693.7101289	9.1278919
1	457.8854805	168.8636957	5	693.8333318	0.1232029
2	613.6762507	155.74777026	6	693.8333537	$2.19 \times 10^{-5}$
3	684.582237	70.9059863			

Now, using  $\lambda^* = 693.833$  and Equation (2), we calculate the unique optimal solution  $x^*$  to the continuous relaxation model to be

(2.600, 3.496, 2.624) min  $z = \sum_{i=1}^{n} c_i x_i^* = 21.770$ . Rounding up z, we get 22, a lower bound for optimal objective value of discrete model, and rounding up coordinates of the optimal solution to the relaxed model, we get (3,4,3) which is feasible for the discrete model, and the objective value of this feasible solution is 25 which is an upper bound for the optimal objective

#### value of the discrete model.

**Note**: In general, the feasible solution obtained by rounding up the coordinates of the optimal solution of the relaxed model is not optimal. Using the reduction procedure in Nmah [18], we get (3,3,3) which yields z = 24.

As in Nmah[18], we know that  $x_i \geq xmin_i$  for  $i = 1, 2, 3, \dots, n$  for any feasible solution. Particularly for our case,  $xmin_i = 3$  for i = 1, 2, 3. So, (3, 3, 3) is optimal with z = 24.

**Note**: We observe that Rice et al [2] achieved the same result but by a different method.

### Conclusion

The main result of this work is to solve a relaxed minimum-cost problem by showing that from an initial value determined by the model's parameters, Newton's method finds the optimal value,  $\lambda^*$ , of the Lagrange multiplier. In Section 2 we found upper and lower bounds for the roots,  $\lambda^*$ , of equation (3), and proved that the optimal Lagrange multiplier  $\lambda^*$ , satisfies  $\lambda_{min} \leq \lambda^* \leq \lambda_{max}$ . Nmah ([1] and [2]) proved that the vector  $x^*$  and the positive multiplier  $\lambda^*$  that satisfy equations (2) and (3) are unique, and we showed in Section 3 that the optimal Lagrange multiplier  $\lambda^*$  is the unique zero of the  $C^2((0,\infty))$ -function h defined in Section 3. Also in Section 3 we showed how to approximate  $\lambda^*$  by Newton's method. Finally, in this Section we used two examples to illustrate the method.

### Acknowledgement

The author would like to thank the staff of the Atlanta University Center Woodruff Library for their invaluable services. The author would also like to thank the referees for their helpful suggestions and comments that help to improve this original research manuscript.

### **Competing Interests**

The author has declared that no competing interests exist.

#### References

- [1] Nmah B. Optimizing system reliability with integer programming, New Mexico State University: UMI Dissertation Services, Bell & Howell Company, 1997
- [2] Nmah B, Optimal allocation of redundancy in a mixed system, International Journal of Pure and Applied Mathematics, Vol 73, No. 3, 2011, 255-265
- [3] Leon F, Cascaval P. Optimization methods for redundancy allocation in complex system. 23rd International Conference on System Theory, Control and Computing, 2019
- [4] Rice W., Cassady C., Wise T. Simplifying the solution of redundancy

- allocation problems, 1999 Proceedings Annual Reliability and Maintainability Symposium, , pp190-194
- [5] Kuo W., Wan, R. Recent advances in optimal reliability allocation, Coput Intelli in Reliability Engineering, Springer Berlin, 2007, pp1-36
- [6] Japan Standard Association. Reliability guidebook, Asian Productivity Organization, 1972
- [7] Tillman F., Hwang C., Kuo W. Optimization techniques for system reliability with redundancy: A review, *IEEE Transactions on Reliability*, Vol R-26, No. 3, Aug 1977, 148-155
- [8] Tillman F, Hwang C., Kuo W. Optimization of system reliability, Marcel Dekker, INc. 1980
- [9] Devi S. Garg H., Garg D. A review of redundancy allocation problems for two decades, bibliometrics and future directions, Artificial Intelligence Review, 2023, 56, 7457-7548
- [10] Elsayed E.A., Reliability Engineering, 3rd edition, John Wiley & Sons, Inc., 2021
- [11] Chern MS. On the computational complexity of reliability redundancy allocation in series systems, Operation Research Letters, 1992; 11:309-315
- [12] Ushakov I. Optimal resource allocation: with practical statistical applications and theory, First Edition, John Wiley & Sons, Inc, 2013
- [13] Li Y, Zio E, Kleyner A. System reliability assessment and optimization: methods and applications (e-book), John Wiley & Sons, Inc, 2022
- [14] Leon F., Cascaval P., Badica C. Optimization methods for redun-

- dancy allocation in large sysyems, Vietnam Journal of Computer Science, Vo 7, No. 3 (2020) 281-299
- [15] Allen III, B, Isaacson L. Numerical analysis for applied science, John Wiley & Sons, Inc.,2019
- [16] Henrici P. Elements of numerical analysis, John Wiley & Sons, Inc., 1964
- [17] Lebl J., Introduction to real analysis, Volume I, CreateSpace Independent Publishing Platform, 2018. ISBN 9781718862401
- [18] Nmah B. Shorter searches for least-cost allocation of redundancy. American Journal of Scientific and Industrial Research. 2015; 6(6):116-122.