Original Research Article

Effect of different levels of irrigation on yield and yield attributes of Marigold crop (*Tagetes erecta L.*)

Abstract

Agriculture has been indispensable for the subsistence of the people of India in general and farmers in particular. It has naturally been the cornerstone of the Indian economy since time immemorial and agriculture has played a major role in the country's economy since its inception. The research work was done to study the effect of irrigation levels on the yield and growth of winter marigolds. Marigold (Tagetes erecta L.) had been taken twice the winter season of 2019-20 and 2020-21. The average flower yield (t/ha) was recorded under the treatment I₁ (12.03 t/ha) was found maximum and it was followed by I₂ (10.51 t/ha), I₃ (9.73 t/ha). The consumptive water use (CWU) was found maximum (26.62 cm) in 100% of ET_c and the lowest CWU was found (21.03 cm) in 80% of ET_c through a drip system of irrigation in the cropping year 2020-21. Similarly, in 2019-20 CWU was found maximum (18.02 cm) in 100% of ET_c, while the lowest CWU was found (14.42 cm) in 80% of ET_c. The water use efficiency was found highest in I₃ (0.77 t/ha/cm) and minimum WUE was found in I₂ (0.525 t/ha/cm) in the cropping year 2019-20. For 2020-21, a maximum WUE was recorded in I₂ (0.497 t/ha/cm) and the minimum WUE in I_3 (0.335 t/ha/cm).

Introduction

Water has always been an essential component of human existence, and it is available in limited form from natural resources. Our population increase continuously, and they affect the limited natural resource directly. The agriculture sector has used a huge amount of fresh water, so it is very important to utilize natural resources carefully. Different irrigation methods are used in agriculture; micro-irrigation is one of the best suitable methods for getting high water use efficiency. (FAO, 2017)

India is mostly a farming country, and Agriculture employs around 70% of our population and accounts for one-third of our national income. Recently the share of the agriculture sector in the national GDP has risen to 20% (NSO, India, 2021).

Micro-irrigation systems such as the drip irrigation system that helps to save 27 to 42 per cent of water. It helps to increase water use efficiency by reducing soil evaporation and drainage losses. Evaluation of hydraulics of drip irrigation systems helps improve irrigation system design and better control of irrigation water. Its field application efficiency can be up to 90%, compared to 60-80% for sprinklers and 50-60% for surface irrigation. (Gorantiwar *et al.*, 1991).

A large amount of plastic waste is generated from the food items used every day. Due to which there is land pollution, water pollution and air pollution in large quantities. Recycling plastic waste has become very expensive and difficult but reusing is a good way to reduce plastic waste (Odabasi and Uyukgungor, 2016). Almost every farmer in Chhattisgarh has a piece of land called Biyara, used as a threshing floor after harvesting the crop. That piece of land remains unusable for a whole year after some time. Using this land for production without ploughing the field and farming can be done using less water.

This research has been prepared to look at all the points like the judicious utilization of precious water resources, judicious utilization of reusable plastic bags, saving water, and keeping in mind the Chhattisgarh government's Narva, Garwa, Ghurva and Bari schemes. In which stored rainwater is used for irrigation and solar energy is used to pump that stored water. For a kitchen garden, barren and unfertile land, a portable plant growing system had been developed using waste plastic material to be easily collected in our society. The research work was done to study the effect of irrigation levels on the yield and growth of winter marigold. Marigold (*Tagetes erecta L.*) had been taken twice the winter season of 2019-20 and 2020-21.

Materials and Methods

Study area

The experiment was laid out at Dept. of SWE, IGKV, Raipur, to cultivate winter Marigold with solar power operated improvised drip system of irrigation. Raipur is situated in the central part of Chhattisgarh. The experimental site is located at Latitude 21°14′6″ N and Longitude 81°43′10″ E and an altitude of 302 meters above the mean sea level. An area of 261 m² (18 x 14.5 m) of the experiment had been considered for the study. *Pusa-Narangi* variety of Marigold was taken into consideration for cultivation. Seeds were sown in the nursery and 25 days old seedlings were transplanted to the main field, i.e. Reusable flour bags, Conventional grow bags and Plastic bottles.

Weather data of the study area during 2019-20

The weather data recorded during the investigation period from 13th December 2019 to 30th March 2020. The maximum temperature during the experiment varied between 21.3 °C to 35.8 °C, and the minimum temperature varied between 10.8 °C to 22.1 °C. The maximum rainfall during the period of the experiment was 35.8 mm. The average maximum relative humidity for different months varied from 75.9 to 93.6 %, while monthly average minimum relative humidity varied between 27.3 to 56.3 %. The average sunshine values varied from 2.4 to 9.8 hours, maximum wind velocity during the crop period was 4.1 km hr⁻¹ and the minimum was recorded 1.6 km hr⁻¹. (Dept. of Agrometreology, IGKV. 2020)

Weather data of study area during 2020-21

The weather data recorded during the investigation period from 2nd December 2020 to 26th March 2021. The maximum temperature during the experiment varied between 27.7 °C to 37.9 °C whereas, the minimum temperature varied between 9.2 °C to 20.1 °C. The maximum rainfall during the period of the experiment was 6.2 mm. The average maximum relative humidity for different months varied from 58.3 to 88.7 %, while monthly average minimum relative humidity varied between 14.3 to 40.6 %. The average sunshine values varied from 3.2 to 9.5 hours, maximum wind velocity during the crop period was 4.2 km hr⁻¹ and the minimum was recorded 1.4 km hr⁻¹. (Dept. of Agrometreology, IGKV. 2021)

Treatment Details

To study the effect of irrigation levels, three different irrigation levels like I₁-100% ET_c, I₂- 90% of ET_c and I₃- 80% of ET_c were selected as the main plot, and three types of plastic grow containers like M₁- Reusable flour bag (RFB), M₂- Conventional grow bag (CGB), M₃- Plastic bottle (PB) were selected as a subplot and having a split-plot design with three replications had been adopted. In each replication, 540 plants of winter Marigold crop at 30 cm plant to plant spacing, whereas 50 cm row to row spacing has been planted for experimentation. Irrigation was provided based on (ET_c) using soil and agrometeorological parameters. The prepared field and other details are shown in Table 1.

Plant growing media

All grow containers were placed according to the layout design and filled with soil, FYM and coco-peat in the ratio of 40:40:20, respectively. Physico-chemical properties of the prepared media were tested in the Dept. of soil science laboratory, IGKV, Raipur. The ratio of prepared media was found better for horticulture crop by Nair and Bharathi (2015), and Agrawal *et al.* (2020).

Improvised Drip Irrigation System

The improvised drip irrigation system (IDI) helps to keep the soil surface dry and reduces water evaporation, thus saving water and improving fertilizer uptake. The dry soil significantly reduces weed development and plant diseases, increases the dripline's lifetime, and protects it from mechanical and environmental damage. Arrangement of lateral lines over the grow containers is very difficult and emitter positions change continuously when lateral lines are displaced. So durable improvisation is necessary for the emitter position and stability of lateral lines. A small (18 mm) hole is made in all grow containers and laterals are placed 5 cm into the grow containers to solve this problem.

A drip irrigation system with a lateral size of 16 mm of 18 m length, $1.3 l h^{-1}$ emitters (inline) at 1 kg/cm^2 at 30 cm spacing (60 number of emitter per lateral) was used to study hydraulic performance. Irrigation water was supplied from the

2000-litre storage tank, 0.1 hp solar operated pump was used to lift the water stored in the storage tank. The flow rate or discharge of the emitter was collected directly in the measuring cylinder. Discharge of emitters concerning test time was converted into discharge per hour.

Irrigation water requirements

Crop evapotranspiration is the amount of water that is lost through evapotranspiration. The actual evapotranspiration was estimated by multiplying reference evapotranspiration and crop coefficients for the different periods based on crop growth stages. Reference evapotranspiration (ET₀) was calculated using a Penman-Monteith method (Doorenbos and Pruitt, 1977) with the help of meteorological data recorded by the meteorological observatory of Indira Gandhi Krishi Vishwavidyalaya, Raipur (C.G.). The plants were irrigated daily by drip irrigation systems. The crop coefficient (Kc) for different growth stages of marigold was considered based on the unpublished report and local studies carried out in India.

$$IR = (ET_0 \times K_c) - R \tag{1}$$

$$V = IR \times A \tag{2}$$

Irrigation time (hours day⁻¹) = $\frac{\text{water requirement in litre per day}}{\text{rate of application litre per hr}}$

 $IR = net depth of irrigation (mm day^{-1})$

 ET_0 = reference Evapotranspiration (mm day⁻¹)

 $K_c = crop coefficient$

R = rainfall (mm per day)

 $V = \text{net volume of water required by a plant } (m^3 \text{ day}^{-1})$

A = area under each plant (m²)

Yield Calculation

Marketable and total flower yield tone per hectare was worked out with the help of flower yield per plot by using the following formula:

Yield (t/ha) =
$$\frac{\text{weight of flower in kg/plot } \times 10000}{\text{plot area} \times 1000}$$
 ...(3)

Statistical Analysis

The experiment was laid out in a split-plot design (SPD). The data obtained from the various characters under study were analyzed by analyzing variance described by Gomez and Gomez (1984). To compute the mean value of treatments, standard error and critical values were calculated as follow:

1. Standard error of the mean

$$SEm = \pm Ve$$
 ... (4)

2. Critical difference (CD)

$$CD = SE (d) \times t \text{ value at 5\% error (df)}$$
 ... (5)

Result and Discussions

The solar power water distribution system incorporates a special solar pump with a portable 150-watt solar panel. A cost-effective and minimal carbon emission portable plant growing system was developed; no-tillage operations were required to cultivate the marigold crop. The result revealed that farming is possible in barren and infertile land using waste plastic bags for cultivating flower crops helps to reduce water and carbon footprints. With the help of Reusable plastic bags like 5 to 10 kg *Atta* bags, conventional grow bags and 2-litre plastic bottles, a sustainable plant growing system was developed for barren and infertile land.

Irrigation efficiency

Emission uniformity of the system decides the uniform distribution of discharge by each emitter or uniform distribution of water to each plant. The calculated emission uniformity data in a solar power operated improvised drip irrigation at 0.25 kg/cm² operating pressure has been presented in Table 2. The maximum average emission uniformity of 98.35 % was observed. The maximum

application efficiency and distribution efficiency were found at 95.62 % and 98.80 %, respectively, at 0.25 kg per cm² operating pressure.

Nursery preparation of marigold

A nursery for winter marigold (*Tagetes erecta L*.) for this experiment was prepared by Horticulture Department, IGKV, Raipur, in which nursery beds of dimensions 1.0 m x 4.0 m (width x length) was prepared. Healthy seeds were sprinkled in rows on nursery beds prepared by pulverizing soil, mixed with farm yard manure (FYM) at the rate of 250 kg ha⁻¹. When needed, water was given at intervals of a few days. The entire nursery bed was covered with paddy straw for proper germination and to avoid weevils. After germination, all paddy straws were removed and left uncovered. Good quality seedlings were ready after about 28 days and were ready for transplanting

Effect of different levels of irrigations on crop growth and yield parameters

The following observations were recorded during the crop growth period on five randomly tagged competitive plants from each plot of every replication for studying various characters, i.e. growth character, flowering, and yield and it is shown in table 3 & 4.

Plant height (cm)

The average values of marigold plant height (cm) for both years, i.e. 2019-20 and 2020-21, at different crop growth stages after transplanting, as influenced by the different irrigation levels and grow containers, are described herein. For two years, experimented plant height data had been analyzed at 30 days after transplanting (DAT), 60 DAT, and 90 DAT. All data is shown in Table 3.

At 30 DAT, the plant height in treatment I_1 (15.92 cm) is higher than in treatment I_2 (15.80 cm) and I_3 (15.71 cm), respectively. At 60 DAT, the plant height in treatment I_1 (44.50 cm) is higher than in treatment I_2 (44.17 cm) and I_3 (43.02 cm), respectively. At 90 DAT, the plant height in treatment I_1 (79.56 cm) is higher than in treatment I_2 (77.92 cm) and I_3 (76.41 cm), respectively. Plant height (cm) at 30 DAT showed no significant difference (p>0.05) and plant height (cm)

with CD value 0.40 at 60 DAT showed a significant difference (p<0.05). Similarly, no significant difference (p>0.05) was found in plant height (cm) at 90 DAT of the marigold crop at three different irrigation levels.

Number of branches

Data on a number of branches at different growth stages of the marigold plant after transplanting as influenced by the different irrigation levels are shown in Table 3.

A slightly higher number of branches at 30 DAT was recorded under the treatments I_1 (1.33) followed by I_2 (1.32) and I_3 (1.29). At 60 DAT, the maximum number of branches was recorded under the treatment I_1 (7.68) and it was followed by I_2 (7.61) and I_3 (7.39), respectively. Similarly, at 90 DAT higher number of branches was recorded under the treatment I_1 (9.41) and it was followed by I_2 (9.26) and I_3 (9.18), respectively.

Statistical analysis shows a significant difference (p<0.05) in the number of branches with a CD value of 0.015 at 30 DAT. With a CD value of 0.059 at 60 DAT, statistical analysis shows a considerable difference (p<0.05). Similarly, in 90 DAT significant difference (p<0.05) was found with a CD value of 0.19.

Number of days of first budding

The treatment I_1 (46.33) had the number of days of first budding, followed by I_2 (46.57) and I_3 (48.61). Statistical analysis shows a significant difference (p<0.05) in the number of days of first budding of the marigold crop with CD value 1.09 at three different irrigation levels.

Number of days of first flowering

Under the different levels of irrigation, I_1 (55.54) had the highest number of days of first flowering, followed by I_2 (56.50) and I_3 (59.17), respectively. Statistical analysis shows a significant difference (p<0.05) in the number of days of first flowering with CD value 1.674 of the marigold crop at three different irrigation levels.

No of picking days

A slightly higher number of picking days were recorded under treatment I_1 (8.98), which was followed by treatments I_2 (8.44) and I_3 (7.89). Statistical analysis reveals a significant difference (p<0.05) in the number of picking days for the marigold crop at three different irrigation levels, with a CD value of 0.406.

The average diameter of the flower (cm)

The treatment I_2 (3.47 cm) produced a considerably larger flower diameter than the treatment I_1 (3.34 cm) and I_3 (3.26 cm), respectively. Statistical analysis reveals a significant difference (p<0.05) in the average diameter of the flower in the marigold crop at three different irrigation levels, with a CD value of 0.121.

Number of flowers per plant

The treatment I_1 (43.16) had the highest number of flowers per plant, followed by I_2 (40.87) and I_3 (38.11), respectively. Statistical analysis shows a significant difference (p<0.05) was found in the number of flowers per plant with a CD value of 0.901 in the marigold crop at three different irrigation levels.

Average yield per plant (gm)

A slightly higher average yield per plant was recorded under the treatment I_1 (175.10 gm) and it was followed by I_2 (158.15 gm) and I_3 (139.46 gm), respectively. Statistical analysis shows a significant difference (p<0.05) on avg. yield per plant (gm) with CD value 2.643 in the marigold crop at three different irrigation levels.

Average yield per plot (kg)

A slightly higher average yield per plot was recorded under the treatment I_1 (3.50 kg) and it was followed by I_2 (3.16 kg) and I_3 (2.79 kg), respectively. Statistical analysis shows that there is a significant difference (p<0.05) was found on Avg. yield per plot (kg) with CD value 0.053 in the marigold crop at three different irrigation levels.

Average flower yield (t/ha)

Significantly avg. flower yield (t/ha) was recorded under the treatment I_1 (11.67 t/ha) was found maximum and it was followed by I_2 (10.61 t/ha) and I_3 (9.28 t/ha). Statistical analysis shows a significant difference (p<0.05) was found on avg. flower yield (t/ha) with CD value 0.175 in the marigold crop at three different irrigation levels.

Consumptive water use and water use efficiency

The consumptive water use (CWU) was found maximum (26.62 cm) in 100% of ET_c and lowest CWU was found (21.03 cm) in 80% of ET_c through a drip system of irrigation in cropping year 2020-21. Similarly, in the year 2019-20 CWU was found maximum (18.02 cm) found in 100% of ET_c, while lowest CWU was found (14.42 cm) in 80% of ET_c. The water use efficiency was found highest in I_3 (0.77 t/ha/cm) and minimum WUE was found in I_2 (0.525 t/ha/cm) in the cropping year 2019-20. For 2020-21, a maximum WUE was recorded in I_2 (0.497 t/ha/cm) and the minimum WUE in I_3 (0.335 t ha⁻¹ cm⁻¹).

Conclusions

In I_1 (100% ET_C) and I_2 (90% ET_c) irrigation levels, the maximum plant growth was observed, while slightly good plant growth was found in the I_3 (80% ET_c) irrigation level. Due to favourable plant growth conditions and better spectral distribution of root growth, marigold plants in Reusable flour bags (RFB) at different irrigation levels had a favourable influence on morphometric features and other yield parameters.

References

- Agrawal, R. 2020. Development and performance evaluation of hydroponic systems with different media and irrigation methods. Ph.D. Indira Gandhi Krishi Vishwavidyalaya, Raipur
- Doorenbose, J. and Pruitt, W.O. 1977. Crop water requirements. FAO irrigation and drainage paper 24:1-156.
- FAO, 2017. A report produced for the G20 Presidency of Germany. Water for sustainable food and agriculture. http://www.fao.org/nr/water/docs/water at a glance.pdf)
- Gomez, K., A. and Gomez, A.A. 1984. Statistical procedures for agricultural research. An international rice research institute book. John wiley & sons, New York, p. 680.
- Gorantiwar, S. D., Pingale, L. V., Pampattiwa, P.S., Pagar, V. W. and Sardesai, M.A. 1991. Evaluation of drip irrigation for lady's finger (*Abelmoschus esculentus* M). *Maharashtra J. Hort.* 5(2): 93-97.
- Nair, A. S., and Bharathi, T. U. 2015. Influence of potting media composition on pot mum production. The Bioscience, 10(1), 73-76.
- National statistics office, Ministry of statistics and program implementation, Government of India. 2021.
- Odabasi, S. U. and Buyukgungor, H., 2016. PET water bottle: A carbon footprint assessment. 1st International Black Sea Congress on Environmental Sciences (IBCESS). TURKEY-31st August to 03rd September, 2016.

Table. 1 Details of different treatments

Main plot: Irrigation levels							

Table 2: Irrigation efficiency at 0.25 kg/cm² operating pressure.

Uniformity coefficient		Application	efficiency	Distribution efficiency		
S_q	0.011	Q _{mini}	0.811	$q_{\rm m}$	0.837	
$q_{\rm m}$	0.837	Q_{avg}	0.837	q_a	0.010	
Uc (%)	98.59	E _a (%)	96.86	E _d (%)	98.80	

Table 3: Plant height, number of branches, first budding and flowering of marigold plant at pooled data of 2019-20 and 2020-21.

Levels of irrigation	Plant Height (cm)		Number of branches			First Budding	First Flowering	
% ET _c	30	60	90	30	60	90	day	day
	DAT	DAT	DAT	DAT	DAT	DAT		
I_1	15.92	44.50	79.56	56.06	7.68	9.41	46.33	55.54
I_2	15.80	44.17	78.96	56.27	7.61	9.26	46.57	56.50
I_3	15.71	43.02	77.89	59.11	7.39	9.18	48.61	59.17
SE (d)	0.073	0.141	0.538	0.005	0.021	0.067	0.382	0.587
SE (m)	0.051	0.1	0.38	0.004	0.015	0.047	0.27	0.415
CD (5%)	0.16	0.401	N/A	0.015	0.059	0.19	1.09	1.674

Table 4: A marigold plant's growth and yield attributes at pooled data of 2019-20 and 2020-21.

Levels of irrigation	Picking days	Average diameter of the flower	Number of flowers	Yield per plant	Yield per plot	Yield per plant	Water use efficiency
% ET _c		cm		gm	kg/plot	t/ha	t/ha/cm
$\overline{I_1}$	8.98	3.50	43.16	175.10	3.50	11.67	0.54
I_2	8.44	3.36	40.87	158.15	3.16	10.61	0.55
I_3	7.89	3.23	38.11	139.46	2.79	9.28	0.55
SE (d)	0.142	0.042	0.316	0.927	0.019	0.061	0.004
SE (m)	0.101	0.03	0.223	0.656	0.013	0.043	0.003
CD (5%)	0.406	0.121	0.901	2.643	0.053	0.175	0.012