

Impact of rainfall trend on irrigated agriculture of Narayanapura Command

ABSTRACT

Water demands have been exacerbated by the uncertainty in rainfall occurrences and distribution due to various factors in a changing climate and growing population. The irrigation sector has the highest water demand, accounting for 85 percent of total water use in Karnataka. Rainfall plays a critical part in meeting irrigation needs. If reliably predicted, consistent rainfall can augment agricultural water requirements, a significant portion of irrigation resources can be saved. Hence, it is required to examine rainfall patterns, distribution of rainfall trends, and both regional and temporal variations in order to efficiently allocate and manage water resources for command area management.

Using two significant time-series statistical trend tests, this research attempted to analyze the Spatio-temporal distributions of long-term rainfall patterns for the Narayanapura Command region. For spotting monotonic trends in time series data, the non-parametric rank-based statistical Mann–Kendall (MK) test and the Innovative Trend Analysis (ITA) method are applied. The results are then geo-processed to examine the spatial distribution of trends using the isohyetal concept. The findings illustrate the spatial distribution of rainfall trend for the command in a semi-arid region on a monthly, monsoon, and annual basis. The spatial and temporal fluctuations are evaluated, and pattern behavior is studied. Further, the impact of the such changes is analyzed on irrigation water requirements.

Spatio-temporal analyses from both methodologies indicates the trend in rainfall pattern is decreasing annually and in monsoon months, with a rising trend for pre-monsoon showers. The trend variation pattern also reveals periodic oscillation alignment in the direction of Southwest monsoon movement. According to MK test results, monsoon rainfall is anticipated to decrease by 12 percent by 2047, and by 21 percent from ITA results. According to the estimate, for every unit millimeter of rainfall deficit, there would be a 62 ha-m increase in irrigation water demand.

Keywords: Climate change impact on effective rainfall, crop water requirements, gross irrigation requirements, MK test, ITA method, rainfall trend

1. INTRODUCTION

In India, 38% of the country's geographical area falls under semi-arid regions and 16% of the area is arid [1]. In these semi-arid regions, the major source of rainfall is from south-west monsoons. Precipitation plays a significant role in irrigation management, particularly in the arid and semi-arid regions. Rainfall is the major source of water for agriculture, both directly on planted fields as incident effective rainfall and indirectly through surface and groundwater irrigation sources. Irrigation supplies are decided based on dependable rainfall patterns. Long-term rainfall records are used to calculate effective rainfall based on the likelihood of

occurrence, and irrigation water conveyance and distribution systems are then designed to supply the crop's water shortfall. Because rainfall varies from year to year under climate change scenarios, long-term rainfall data must be updated to reflect current changes in rainfall behavior, and extreme rainfall conditions must be forecasted and factored into irrigation structure designs. Such approaches in agriculture play a critical role in increasing resilience to climate change. In recent years, several studies have been conducted to determine possible climate trends and changes around the globe, analyzing changes in temperature and rainfall [2]. The major impact of climate change is the change in rainfall patterns. Changes in rainfall due to global warming will have an impact on water demand especially in agriculture, which requires a review of hydrologic design and management practices [3].

Various statistical tests are used to determine trends in hydrological and hydrometeorological time series; these are classified as parametric and nonparametric tests [4]. The parametric test has great potential but requires independent data and is normally distributed, which is rarely true with the details of a hydrological time series. In non-parametric tests, data should be independent and outliers are more tolerable to these tests [5]. The Mann-Kendall trend test [6,7] is one of the most widely used non-parametric tests to find significant trends in the time series. The Mann-Kendall trend test is not affected by the actual distribution of data and is not very sensitive to outliers [8].

Innovative Trend Analysis (ITA) is a method of working based on a timeline from a series of times given to the cartesian coordinate system to perform trend analysis to overcome issues in Mann-Kendall (MK) and Spearman's rho (SR) tests [9]. Potential trends in monthly and seasonal rainfall patterns have been investigated by ITA, which allows for the detection of a low, medium, and high-value series [10]. The trend of annual rainfall variability was analyzed using ITA by comparing its output with the MK and Sen's slope test [11]. Use of ITA analysis for time series data based on sub-samples from the same time series without assumptions [12]. Central India's rainfall patterns were tested on monthly, annual, and annual estimates using the Revised Mann-Kendall (RMK), Sen's slope test, and innovative trend Analysis [13]. Investigates geographical and trend patterns for certain seasons (pre-monsoon, monsoon, post-monsoon, and winter) and annual rainfall series data [14]. This study also contributes to the ITA approach by extensively exploring the styles of the various phases of the timeline [15]. However, the concept of spatial variability of results from MK Test and ITA method along with time needs to be explored to assess the regional changes in rainfall patterns at command area level.

Under the influence of climate change, regional strategies are essential in planning sustainable water resource management. Climate change has a direct impact on crop output and irrigation water supply due to changing rainfall patterns over time. Trend tests are used to study the rainfall patterns under changing climate and crop water requirements are computed for the forecasted conditions in order to examine the impact of rainfall availability on irrigation water demand [16-20].

Hence, this study was carried out with the following specific objectives: (i) to analyze the temporal trend of monsoon and annual rainfall time series data using the MK and ITA method; (ii) to compare the results of the MK method with the ITA; and (iii) to assess the impact of rainfall pattern on irrigation water demands.

2. STUDY AREA AND DATA

The focus of this study is on the command area of Narayanapura Canal (NLBC). The command under NLBC extends from Longitude 76° 28' 58.3" E to 76° 35' 40" E and Latitude

16° 30' 49.6" N to 16° 33' 11.3" N (Refer Figure 1). The Study area lies in the North Karnataka region of India characterized by Semi-Arid climate. The data collected for this study consists of daily rainfall data from raingauges in and around the study area, cropping pattern from project sources, evapotranspiration and crop co-efficients values from India Meteorological Department (IMD) for agroclimatic zone 2.

Long-term daily rainfall data of seven rain gauge stations in and around the command area is collected for a period of 58 years from 1960-2017. The locations of raingauges and attributes are as given in Table 1. The cultivable command area (CCA) is 47,223 hectares. The principal crops grown in this command are paddy, cotton, pulses and sorghum. The cropping pattern is primarily paddy occupying 46.8% of CCA followed by cotton with 28.5%, pulses by 14.1% and sorghum by 10.6%.



Figure 1: Study area map with influencing rain gauges.

Table 1: Raingauge locations for the Study area.

Sl. No.	Stations	Latitude	Longitude	Monsoon RF in mm		Annual RF in mm	
				Mean	SD	Mean	SD
1	Deodurga	16° 24 ' 53"	76° 56 ' 04"	514.92	171.90	732.51	242.42
2	Jewargi	17° 00 ' 51"	76° 46 ' 27"	563.06	221.40	779.46	280.27
3	Lingsugur	16° 09 ' 22"	76° 31 ' 21"	389.66	131.71	604.03	184.25
4	Muddebihal	16° 19 ' 57"	76° 08 ' 02"	378.11	133.88	594.51	173.88
5	Shahapur	16° 42 ' 10"	76° 50 ' 22"	594.62	240.73	841.05	281.82
6	Shorapur	16° 31 ' 07"	76° 45 ' 39"	503.16	217.68	716.54	291.35
7	Sindgi	16° 54 ' 58"	76° 14 ' 13"	452.40	146.57	637.39	188.74

3. METHODOLOGY

Statistical trend analysis for long-term Rainfall data along with spatiotemporal distribution mapping in the GIS platform is attempted in this study for the identified Study area. This is further attributed to the impact of Irrigation water requirements in the command area.

In this study the sensitive trends in rainfall pattern are compared between two statistical methods. The trend analysis of the rainfall is carried out for monsoon season and crop base period months using two statistical methods i.e., the Mann-Kendall Trend Test (MK Test) and Innovative Trend Analysis (ITA) method. The sensitive trends in rainfall patterns are compared using two statistical methods in this study. In many instances, the MK test limits itself to detect sensitive trends, in which case the ITA approach is a viable alternative [21-22]. The trends in rainfall pattern are assessed with appropriate confidence limits and used to compute the impact on irrigation water demand. The flowchart of the processes involved in this study is indicated in Figure 2.




Figure 2: Flowchart for computation of impact of rainfall trend on Irrigation water requirements.

3.1 Mann-Kendall Test

The Mann-Kendall Trend Test is a non-parametric test popularly used for detecting increasing or decreasing trends in time series data. Assessment of the monotonic trends (i.e., increasing or decreasing) in the time series data is evaluated depend upon the normalized test statistics value called Z. The time series data is assessed for the trend at various significance levels by varying alpha (0.05 is the default).

MK test compares the relative magnitudes of data rather than the data values themselves. In this test, each figure of data in a timeline is matched to all subsequent data figures. Initially, the MK statistics (S) value is to be considered zero, and if the value of data in subsequent periods is higher than the data value in the last period, S is increased by 1, and vice versa. The net outputs of all changes from zero give the final value of S.

The Mann-Kendall statistics (S) is given in the equation below:

$$S = \sum_{i=1}^{n-1} \sum_{j=i+1}^n \text{sign}(x_j - x_i) \quad (1)$$

Where,

n = Total number of observations;

x_i = Rank for i th observations ($i = 1, 2 \dots n - 1$);

x_j = Rank for j th observations ($j = i + 1, 2 \dots n$);

and sign function is computed as:

$$\text{sign}(x_j - x_i) = \begin{cases} 1; & \text{if } (x_j - x_i) > 0 \\ 0; & \text{if } (x_j - x_i) = 0 \\ -1; & \text{if } (x_j - x_i) < 0 \end{cases} \quad (2)$$

The test statistic S is assumed for the series where sample size $n > 10$ is asymptotically normally distributed with mean $E(S)$ and variance $\text{Var}(S)$ as:

$E(S) = 0$, and

$$\text{Var}(S) = \frac{n(n-1)(2n+5)}{18} \quad (3)$$

If there is a possibility of a tie in the value of x , the variance is computed as:

$$\text{Var}(S) = \frac{n(n-1)(2n+5) - \sum_{i=1}^P t_i(t_i-1)(2t_i+5)}{18} \quad (4)$$

Where,

P = Number of tied groups indicates the summation over all tied groups; and

t_i = Number of data values in the i th tied group ($i = 1, 2, 3 \dots n$).

After the calculation of $\text{Var}(S)$ of time series data, the standardized Z_{MK} value is calculated using the equation:

$$Z_{MK} = \begin{cases} \frac{S-1}{\sqrt{\text{Var}(S)}}; & \text{if } S > 0 \\ 0; & \text{if } S = 0 \\ \frac{S-1}{\sqrt{\text{Var}(S)}}; & S < 0 \end{cases} \quad (5)$$

The standardized MK test statistic (Z_{MK}) follows the standard normal distribution (Z) with mean zero ($\mu = 0$) and variance one ($\sigma^2 = 1$). For the two-sided condition, the H_0 (null hypothesis) is that which represents no trend in the time series data and H_1 (alternative hypothesis) is that there is a trend in time series data. H_0 and H_1 are tested at a level of significance, $\alpha = 5\%$ with $Z = \pm 1.96$. If $\pm Z_{MK} > Z_{\alpha} = \pm 1.96$, then H_0 is rejected and H_1 is accepted. A negative value indicates a negative trend similarly, a positive value indicates a positive trend in time series data. If the significance level is raised, appropriate Z values are taken into account.

3.2 Innovative trend analysis (ITA) method

The concept of ITA was first proposed by Sen (2012) [8] which was later applied by many researchers [10-15]. The analysis is initially carried out by visual interpretation from drawing the graphs. In this method, time-series data is divided into two halves (first half and second half) from the first to the last time. Then these series of two halves are sorted in ascending order. The first half series (y_i ; $i=1, 2, 3, \dots n/2$) is put on the horizontal axis (i.e., X-axis) and the last half series (y_j ; $j=n/2+1, n/2+2, \dots n$) is put on the vertical axis (Y-axis) as shown in

Figure 3. The scale and range of both axes are kept equal to form a square graph diagram and this square is split into two equal triangles by drawing a 1:1 (45°) line from the origin point of the graph.

A scatter plot of arranged time series data is plotted, the trend in the rainfall pattern is detected based on the position of the data clusters. If the points fall in the upper half of the triangle, then it indicates an increasing trend and if the points fall below the dividing line in the lower triangle, then the rainfall pattern has a decreasing trend. There is no trend in time series data if the points nearly fall on the 1:1 dividing line. The precise distribution of scatter points near or on the 1:1 line indicates weaker trends or no trends. Further [23] the ITA concept is extended to find the trend analysis at different significance levels (1%, 2%, and 10%) to a better understanding of trends in time series data

The trend slope is computed using the following expression [23]:

$$s = \frac{2(\bar{y}_2 - \bar{y}_1)}{n} \quad (6)$$

Where,

s = Trend line slope;

$\bar{y}_2$ and $\bar{y}_1$ = Arithmetic averages of the second and first halves time-series data (y, sequence) respectively; and

n = Total number year for which data considered.

Figure 4 is the graphical representation for understanding the concept of trend slope. After the calculation of the slope of the trend line, the standard deviation of sampling slope is calculated as:

$$\sigma_s = \frac{2\sqrt{2}}{n\sqrt{n}} \sigma \sqrt{1 - \rho_{\bar{y}_1\bar{y}_2}} \quad (7)$$

Where,

σ_s = Standard deviation of sampling slope;

σ = Standard deviation of whole data series; and

$\rho_{\bar{y}_1\bar{y}_2}$ = Cross-correlation coefficient between the ascending sorted two halves arithmetic averages.

The confidence limits (upper and lower) of the trend slope at the significance level (α) are expressed using the following expression:

$$CL_{1-\alpha} = \pm Z \times \sigma_s \quad (8)$$

Where,

$CL_{1-\alpha}$ = Upper and Lower confidence limits at ' α ' significance;

σ_s = Standard deviation of sampling slope.

Z = Z-score

For the two-sided condition, the H_0 (null hypothesis) is that which represents no trend in the time series data and H_1 (alternative hypothesis) is that there is a trend in time series data. H_0 and H_1 are tested at a level of significance, $\alpha = 5\%$ with $Z = \pm 1.96$. If $\pm S > \pm CL_{1-\alpha}$, then H_0 is rejected and H_1 is accepted. A negative value indicates a negative trend similarly, a positive value indicates a positive trend in time series data [23].




Figure 3: Trend in time-series data by a visual interpretation by ITA method.




Figure 4: Slope analysis by the ITA method.

3.3 Crop Water Requirements

Crop water requirements is calculated for the crops in NLBC command and Gross irrigation requirements for the project command is computed using the following standard equations as per Food and Agriculture Organization [24-26]

$$ET_C = ET_O \times Kc \quad (9)$$

$$NIR = ET_C - P \quad (10)$$

$$GIR = NIR / e \quad (11)$$

$$e = \frac{e_c \times e_a}{100} \quad (12)$$

Where,

ET_C = Crop Evapotranspiration (mm),
 ET_O = Reference Evapotranspiration (mm),
 K_C = Crop Coefficient
 NIR = Net Irrigation Requirement (mm)
 P = Effective Rainfall (mm)
 GIR = Gross Irrigation Requirement (mm)
 e = Scheme irrigation efficiency (%)
 e_c = conveyance efficiency (%)
 e_a = field application efficiency (%)

4. ANALYSIS

To carry out the trend analysis, 58 years (1960-2017) of daily rainfall data is considered for 7 rain gauges in and around the study command area. The average rainfall over 58 years indicates that the months January, February, March, April, November, and December has scanty rainfall (Refer Figure 5). Moreover, the kharif crop base period in the command is from May to November. Hence, the analysis and results are focused particularly on the months of monsoon with a buffer month of pre-monsoon showers and post-monsoon which has considerable rainfall. The annual average rainfall is 664.1 mm and the monsoon average rainfall is 450.5 mm. The temporal trend analysis of 7 rainfall stations for monsoon and annual rainfall is found using Mann Kendall (MK) and Innovative Trend Analysis (ITA) methods at various significance levels.




Figure 5: Average monthly rainfall from 1960 to 2017 for NLBC command

4.1 MK Test Analysis

The MK Test trend for time series rainfall data are evaluated for the Pre-monsoon shower month of May; Monsoon months June, July, August, September, and onset post-monsoon month October, as well as overall Monsoon period trends is indicated in Table 2. From the isohyetal plots, the average slope over the NLBC command is calculated using raster analysis. The average Sen's slope of NLBC command for different months is as shown in Figure 6.

Table 2: Sen-Slope of Rainfall pattern using MK-Test for 58 years (1960-2017).

Sl.No.	Rain gauge	May	Jun	Jul	Aug	Sep	Oct	Nov	Monsoon
1	Deodurga	0.38 ^A	-0.12	-0.22	-0.16	-0.02	0.27	0.00	-0.85
2	Jewargi	0.26 ^C	-0.47	-0.84 ^D	-0.49	-0.36	0.05	0.00	-3.00 ^B
3	Lingsugur	0.06	0.12	-0.76 ^A	0.21	-0.89	0.00	0.00	-1.30
4	Muddebihal	-0.03	0.26	-0.47 ^D	-0.06	-0.15	-0.21	0.00	-0.58
5	Shahapur	0.11	-0.62	-0.81	-0.10	-0.95	0.21	0.00	-2.88 ^B
6	Shorapur	0.42 ^A	-0.73 ^B	-0.47	-0.69	-1.32 ^C	0.14	0.00	-3.08 ^B
7	Sindgi	0.00	-0.02	-0.25	0.92 ^B	-0.65	0.01	0.00	-0.06

*^A $\alpha = 5\%$; $Z\alpha = \pm 1.96$

*^B $\alpha = 10\%$; $Z\alpha = \pm 1.645$

*^C $\alpha = 15\%$; $Z\alpha = \pm 1.44$

*^D $\alpha = 20\%$; $Z\alpha = \pm 1.282$




Figure 6: Monthly average Sen's slope (trend) for NLBC command

The average Sen's slope in the command for monsoon season is in decreasing trend at a rate of -1.86mm/year and Annual rainfall is decreasing at a rate of -2.06 mm/year. The months January to April, November, and December have little or no rainfall and the trend is insignificant (refer Figure 6). The pre-monsoon showers month of May has an increasing trend and the monsoon months June to September have a decreasing trend of rainfall pattern (refer Figure 6). It's also worth noting that the sen's slopes are inconsequential in the majority of trends with significance levels ranging from 5% to 20%. A more resilient test is required to detect the sensitive trend in the rainfall pattern with a greater confidence level, which is carried out by the ITA method, in order to validate the trend of the MK test.

4.1.1 Spatial distribution and pattern of rainfall trend by MK Test

The trend results from MK test of raingauges are mapped in the GIS platform using the isohyetal concept to know the distribution and behavior of rainfall trends over the command.

It is observed from the spatial distribution of Sen's slope that the intensity of trend alternatively varies monthly in the direction of South-West to North-East in to and fro pattern. In Figure 7, the green color scale indicates a low-intensity trend and beige to nearly white color indicates a high-intensity trend.




Figure 7: Spatio – Temporal distribution of trend in Rainfall Pattern over NLBC command by MK Test.




Figure 8: Sen's Slope variations of Raingauges for Monsoon months.

As can be observed from the analysis maps, a low intensity increasing trend can be seen in the south-west corner in May, and a high intensity declining trend can be found in the same sector in June. In addition, in July, the same South-west corner has a low-intensity trend, which increases to a high-intensity trend in August and September (refer Figure 7 and Figure 8).

This behavior is occurring exactly in the same alignment as the general path of the South-Western Monsoon passing through this region. Hence, it is found that the intensity with which the rainfall pattern increases or decreases is occurring within the flow direction of the South-Western Monsoon.

4.2 Innovative trend analysis (ITA) method

The primary task in ITA method is to assess the trend in rainfall pattern by plotting scatter graphs for the sorted time series data. The time-series data was divided into two halves first half from the year 1960 to 1989 and the second half for the years 1990 to 2017. This is sorted as per the ITA method and plotted on a scatter graph. The position of clusters is examined for the trend in rainfall pattern. The test is initially carried out with visual interpretation and further slope of the trend is found using applicable equations (refer eq. 6-8).

4.2.1 Visual interpretation of trend in Rainfall pattern for different rain gauges.

Trend analysis is carried out for all 7 Raingauges by the ITA method by visual interpretation from the rainfall pattern plots as shown in Figure 9. According to the scatter plots in Figure 9, most of the points cluster lies in lower half of the 'no trend line'. This demonstrates that the rainfall pattern for the time series data has a negative trend in most of the rain gauges. The peak rainfall months of July, August, and September show a sharp downward trend.

Table 3: Results of ITA method for 7 rain gauges for monsoon months and annual rainfall.

Station	May			June			July			August		
	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits
Deodurga	0.96	0.038	± 0.07	-0.35	0.073	± 0.14	-0.86	0.077	± 0.15	-0.61	0.099	± 0.19
Jevargi	0.30	0.037	± 0.07	-1.00	0.069	± 0.13	-1.69	0.202	± 0.40	-1.08	0.107	± 0.21
Lingsugur	0.04 ^C	0.035	± 0.07	0.48	0.074	± 0.15	-0.99	0.050	± 0.10	-0.41	0.069	± 0.13
Muddebihal	0.19	0.035	± 0.07	0.50	0.040	± 0.08	-0.43	0.052	± 0.10	-0.35	0.053	± 0.10
Shahapur	0.19 ^B	0.101	± 0.17	-0.90	0.094	± 0.18	-1.65	0.074	± 0.15	-0.62	0.064	± 0.13
Shorapur	0.54	0.036	± 0.07	-0.94	0.051	± 0.10	-1.16	0.067	± 0.13	-0.81	0.063	± 0.12
Sindagi	0.23	0.040	± 0.08	0.04 ^C	0.088	± 0.17	-0.24	0.098	± 0.19	0.71	0.112	± 0.22

Station	September			October			November			Monsoon		
	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits	Slope (s)	σ_s	Limits
Deodurga	-1.16	0.160	± 0.31	0.16 ^C	0.276	± 0.54	0.14 ^C	0.104	± 0.20	-2.97	0.199	± 0.39
Jevargi	-1.76	0.136	± 0.27	0.02 ^C	0.080	± 0.16	-0.07	0.048	± 0.09	-5.52	0.223	± 0.44
Lingsugur	-0.64	0.082	± 0.16	0.11 ^C	0.141	± 0.28	0.00 ^C	0.051	± 0.10	-1.56	0.155	± 0.30
Muddebihal	-0.71	0.062	± 0.12	0.36	0.056	± 0.11	-0.35	0.026	± 0.05	-1.00	0.140	± 0.28
Shahapur	-2.22	0.090	± 0.18	0.38	0.166	± 0.33	-0.37	0.112	± 0.22	-5.39	0.339	± 0.66
Shorapur	-2.10	0.157	± 0.31	-0.61	0.248	± 0.49	-0.26	0.082	± 0.16	-5.01	0.270	± 0.53
Sindagi	-1.28	0.064	± 0.13	0.00 ^C	0.131	± 0.26	-0.30	0.039	± 0.08	-0.78	0.120	± 0.24


Note: confidence limits

$\alpha = 5\%$; $Z\alpha = \pm 1.96$ (by default for all figures above except *B and *C)

*B $\alpha = 10\%$; $Z\alpha = \pm 1.645$

*C no Trend

Table 3 shows that in most rain gauges, the rainfall trend is significant with a 95 percent confidence limit, and in a few cases, it is significant with a 90 percent confidence limit (Shahpur rain gauge in May). In May, June, and October, just a few rain gauges show no pattern. This demonstrates that the ITA approach is more effective in detecting subtle changes in rainfall patterns.



x-axis and y-axis are in mm of rainfall.

x-axis is first half of the data timeline 1960 – 1988

y-axis is second half of the data timeline 1989 – 2017

Figure 9: ITA graphs representation for June month rainfall.

4.2.2 Slope by ITA method

The Slope computed from the ITA method is indicated in Table 3. From the spatial distribution plots, the average slope of rainfall pattern by ITA method is calculated for NLBC command and results are tabulated in Figure 10.

The average slope for NLBC by the ITA method shows a decreasing trend at a rate of 3.19 mm/year in the monsoon season and 3.32 mm/year for the annual rainfall pattern. The Pre-monsoon shower month of May has an increasing trend and the monsoon months June to

September has a decreasing trend of rainfall. The post-monsoon months also shows a decreasing trend. (Refer Figure 10).




Figure 10: Average Slope of Rainfall pattern for NLBC command from Isohyetal maps

4.2.2 Spatial distribution and pattern of Rainfall Trend by ITA method

To find the spatial variations in the pattern of trend the slope obtained from the ITA method, the results are plotted in GIS by the Isohyetal method (Refer Figure 11). From Figure 10 and Figure 11 it is observed that there is a decreasing trend of rainfall over the command in the South-west to northeast direction. However, as observed earlier in the case of MK test Sen's slope distribution pattern, the rain gauges in the ITA method also exhibit an alternative sinusoidal pattern in the intensity of the trend in the rainfall pattern (Figure 12). The intensity of trend or the slope value varies between high and low alternatively during the monsoon months.




Figure 11: Spatio – Temporal distribution of trend in Rainfall Pattern over NLBC command by ITA method.




Figure 12: Slope variations of Raingauges for Monsoon months by ITA method.

4.3 Impact on Irrigation requirements

The statistical trend analysis shows that the rainfall pattern has a negative trend in the monsoon months and positive trend in the pre-monsoon month of May. The trend is indicated in Figure 6 and Figure 12. The average rainfall over the NLBC command is computed using isohyets and effective rainfall is computed using USDA soil conservation service method (reference FAO) as indicated in Table 4. The MK and ITA trend are forecasted for 2047 (3 decades) and effective rainfall for the year 2047 is computed (refer Table 4).

Crop water requirements are computed using standard equations (refer eq. 9-11). Gross Irrigation requirement for the command is computed for existing irrigation system efficiency of 45% (refer eq.12). Conveyance efficiency (e_c) for existing canal-lined conditions is 75% (CWC:2014) and application efficiency (e_a) of 60% for surface irrigation method (Brouwer:1989). Regionally published evapotranspiration data, crop co-efficient, and practicing crop seasons for Agro-climatic zone-2 is indicated in Table 6.

Table 4: Effective rainfall for average condition and 3-decadal forecasted condition

Month	Average		MK Test		ITA Test	
	Average Rainfall (mm)	Effective Rainfall (mm)	Rainfall Trend (mm/yr)	Effective Rainfall for 2047 (mm)	Rainfall Trend (mm/yr)	ITA Effective Rainfall for 2047 (mm)
May	38.3	36	0.2	41.2	0.35	41.2
Jun	87	74.9	-0.25	69.4	-0.26	69.4
Jul	91.8	78.3	-0.56	66	-1.01	66
Aug	107.7	89.1	-0.16	86	-0.53	86
Sept	164.1	121	-0.8	108.7	-1.39	108.7
Oct	112.1	92	-0.25	93.3	-0.09	93.3
Nov	23	22.2	0.07	22.2	-0.22	22.2
Total	624	513.5	---	486.8	---	452.6

The crop water requirement is computed for current condition with average rainfall over the command and forecasted trending rainfall as per MK and ITA trends (refer Table6).

Table 5. Inputs for computing Crop water requirements for the command area

Month Fortnight (1)	May I (2)	May II (3)	Jun I (4)	Jun II (5)	Jul I (6)	Jul II (7)	Aug I (8)	Aug II (9)	Sep I (10)	Sep II (11)	Oct I (12)	Oct II (13)	Nov I (14)	Nov II (15)
ETo	113.	121.1	92.40	92.40	73.35	78.24	71.55	76.32	65.40	65.40	70.65	75.36	64.80	64.80
Khariff crops Kc														
Paddy				1.10	1.10	1.10	1.10	1.05	1.05	1.05	1.05	0.95	0.95	
Jowar				0.35	0.58	1.10	1.10	1.10	0.58	0.58				
Pulses				0.35	0.75	1.10	1.10	0.69	0.28					
Cotton		0.35	0.61	0.61	1.13	1.13	1.13	1.13	1.13	1.13	1.13	1.13	0.89	0.65

* As per IMD for Agro climatic zone-2

Table 6. Irrigation demand for the command area using rainfall trend from MK Trend test.

Sl. No.	Crop	Cropped Area in Hectares	% Cropped Area	Days	Total water required			
					Average Rainfall Condition		3-decadal Change	
					in Ha-m	in cumecs	in Ha-m	in cumecs
1	Paddy	22,086.63	46.8%	153.00	44701.27	33.82	46024.17	34.82
2	Cotton	13,463.87	28.5%	199.00	15997.64	9.30	16874.39	9.81
3	Sorgum	4,994.67	10.6%	122.00	2925.80	2.78	3195.39	3.03
4	Pulses	6,677.84	14.1%	92.00	2945.51	3.71	3214.88	4.04
	Grand total	47,223.00	100.0%		66570.21	49.60	69,308.83	51.71

The analysis shows that the impact of rainfall trend on Irrigation demand. The consequences of rainfall pattern shifting to a lower average would result in increase in irrigation water requirements. The decreasing monsoon rainfall pattern would require an additional 2738.62 Ha-m of water to satisfy the agricultural needs (refer table 6). This amounts to 4% increase in water allocation for the command in coming 3-decades. Further, the results show that an additional 4% of discharge has to be accommodated in the canal supplies in 3-decades to supply the additional demand. This is the result of 7% (45 mm) decrease in rainfall during the base period of crops as a common scenario in 3 decades. For unit millimeter of rainfall decrease, nearly 61 ha-m excess water is expected to increase in gross irrigation requirements.

The decreasing monsoon rainfall pattern would require an additional 5869.11 Ha-m (refer table 7) of water to satisfy the agricultural needs. This amounts to 9% increase in water allocation for the command in coming 3-decades. Further, the results show that an additional 9% of discharge has to be accommodated in the canal supplies in 3-decades to supply the additional demand. This is the result of 15% (95 mm) decrease in rainfall during the base period of crops as a common scenario in 3 decades. For unit millimeter of rainfall decrease, nearly 62 ha-m excess water is expected to increase in gross irrigation requirements.

Table 7. Irrigation demand for the command area using rainfall trend from ITA test

Sl. No.	Crop	Cropped Area in Hectares	% Cropped Area	Days	Total water required			
					Average Rainfall Condition		3-decadal Change	
					in Ha-m	in cumecs	in Ha-m	in cumecs
1	Paddy	22,086.63	46.8%	153.00	44701.27	33.82	47728.48	36.11
2	Cotton	13,463.87	28.5%	199.00	15997.64	9.30	17954.62	10.44
3	Sorgum	4,994.67	10.6%	122.00	2925.80	2.78	3268.25	3.10
4	Pulses	6,677.84	14.1%	92.00	2945.51	3.71	3487.96	4.39
Grand total		47,223.00	100.0%		66570.21	49.60	72,439.32	54.04

5. RESULTS AND DISCUSSION

The average rainfall in the command is 450.6 mm in the monsoon season and 664.3 mm annually. Nearly 68% of the average annual rainfall is received in the monsoon season. Such climate is typical to semi-arid zones of India with characteristics of low and erratic rainfall pattern. About 75% of the cropped area 131MHa out of 174 MHa lies in semi-arid regions of the country and highly dependent on rainfall for agricultural needs [27]. Statistical analysis was carried out to assess the possible irregularities in a typical command area of a semi-arid region. Two non-parametric statistical tests, Mann–Kendall test and the Innovative Trend Analysis (ITA) method were carried out and the results were compared to assess the actual vagaries in rainfall pattern for the command area at a regional scale.

In this study, time series Mann-Kendall trend tests indicated that monsoon rainfall in the command is decreasing at a rate of 1.86 /year. Further tests result show that annual rainfall is decreasing at a rate of 2.06/year. Except for a few months, the MK trend tests do not detect most sensitive trends in the 5 percent, 10%, 15%, or 20% confidence limits. As a result, ITA tests were performed to discover the variations in rainfall patterns that were undetected by the MK test. The ITA results likewise reveal similar results to the MK test, but within 5-10 percent confidence limits. The Slope of the rainfall pattern trend by the ITA method also indicates a decreasing trend in monsoon season at a rate of 3.19/year and annually by 3.32/year. On a wider scale, the behavior of decreasing trend in monsoon and annual rainfall for Southwest monsoon areas of India are widely accepted by researchers in their study [28-30] and also indicated in regional publications [31-32]

Monthly statistics from Mann-Kendall Trend tests and ITA test show that there is an increasing trend in Pre-monsoon showers (May). However, there is a declining trend in rainfall patterns for all the months in the monsoon and post-monsoon months. The increase in rainfall trend for the pre-monsoon season and month of May is also observed in regions of North Karnataka [33-34]. The declining trends in individual monsoon months are also shown in various research papers [28,30,32]. The reduction in the post-monsoon rainfall component has an additional impact on rain-fed agriculture and irrigation supplies. The deficiency of monsoon rain has a direct influence on irrigation supplies; if effective rainfall over command decreases, this must be compensated by supplying additional irrigation water for agriculture.

This study also shows that the variations in the magnitude of rainfall trend exhibit periodic seasonal fluctuations in South-West to North-East directions. A similar trend is also observed on a taluk level in the regional publication, where the taluks having a positive rainfall trend in pre-monsoon has a negative rainfall trend at the end of the monsoon [30]. Both statistical trend tests by MK tests and the ITA method provides relatable results for the

command area for detecting and assessing the local trend of rainfall pattern over long-term historical data. The behavior of sinusoidal patterns of rainfall trend also indicates the possible paradigm shift in the rainfall pattern not only during monsoon and annually, but also monthly which leads to possible changes in the regions having more rainfall in monsoon months to fall under the drought conditions in the direction of South-West monsoon movement. It can also be estimated that the intensities of rainfall will vary erratically to satisfy the oscillating behavior of the rainfall trend.

The impact of the decreasing rainfall trend on irrigation demand shows that there is a considerable increase in gross irrigation requirement and discharge in canal (refer table 6,7). This is validated by results from both MK and ITA tests. The results indicate that by MK trend test the rainfall decreases by 7% in 3 decades and accordingly there is 4% increase in water demand. The 3-decadal rainfall decreases by 15% by ITA results and 9% increase in water requirement by year 2047. However, by both the trend methodologies it is observed that for every unit millimeter decrease in rainfall there is 62 ha-m of increase in Irrigation water demand.

5. CONCLUSIONS

The following conclusions are drawn from this research which would aid in planning water resources allocation for irrigated agriculture in command areas of semi-arid zones.

1. MK test and ITA test show complimenting results for rainfall trend. However, in case of sensitive trends ITA test results are more reliable in identifying the rainfall trend for long-term data.
2. Spatial analysis using Isohyetal methods for the trend results can indicate the spatial and temporal variations for different months and trend behavior. In this study, a substantial decreasing trend in monsoon month's rainfall can be observed. It is also found that the temporal variations in rainfall trends fluctuate periodically in the direction of the South-west monsoon path in an oscillating pattern.
3. The decreasing monsoon rainfall has considerable impact on irrigation demand in the command area. In a 3-decadal estimate of climate change trend of rainfall, a unit millimeter of rainfall loss is predicted to increase gross irrigation requirements by almost 62 ha-m. Accordingly, the discharge in the canal has to accommodate additional 2 - 4.5 cumecs of water per 500 sqkm of command.
4. The impact differs depending on the command's cropping pattern and respective crop water requirements. The increase in water demand owing to shifting rainfall patterns is more or less the same for the most commonly grown crops in agroclimatic zone-2. This paper demonstrates the need of taking climate change into account when designing canals to accommodate variations in rainfall patterns over the canal system's lifecycle.

REFERENCES

1. Ajai RR, Arya AS, Dhinwa PS, Pathan SK, Ganesh Raj K. Desertification/Land Degradation Status Mapping of India. *Current Science*. 2009; 97(10), 1478–83.
2. Gocic M, Trajkovic S. Analysis of Changes in Meteorological Variables Using Mann-Kendall and Sen's Slope Estimator Statistical Tests in Serbia. *Global and Planetary Change*. 2013;100,172-182. doi.org/10.1016/j.gloplacha.2012.10.014

3. Anie John S, Brema J. Rainfall Trend Analysis by Mann-Kendall Test for Vamanapuram River Basin, Kerala. *International Journal of Civil Engineering and Technology*. 2018; 9(13):1549–56.
4. Dahmen ER, Hall MJ. Screening of Hydrological Data: Tests for Stationarity and Relative Consistency. 1990; 58.
5. Sneyers R. On the Statistical Analysis of Series of Observations. World Meteorological Organization. 1990;
6. Mann HB. Nonparametric Tests Against Trend. *Econometrica*. 1945;13(3),245–59. <http://www.jstor.org/stable/1907187>.
7. Kendall MG. Rank Correlation Methods. London: Griffin. 1975;
8. Hamed KH. Trend Detection in Hydrologic Data: The Mann-Kendall Trend Test under the Scaling Hypothesis. *Journal of Hydrology*. 2008;349(3–4),350–363. doi.org/10.1016/j.jhydrol.2007.11.009.
9. Şen Z. Innovative Trend Analysis Methodology. *Journal Of Hydrologic Engineering*, 2012;17(9). doi.org/10.1061/(ASCE)HE.1943-5584.0000556.
10. Caloiaro T, Coscarelli R, Ferrari E. Analysis of Rainfall Trend in Southern Italy through the Application of the ITA Technique. *European Water*. 2017;59,199–206.
11. Gedefaw M, Denghua Y, Wang H, Qin T, Girma A, Abiyu A, Batsuren D. Innovative Trend Analysis of Annual and Seasonal Rainfall Variability in Amhara Regional State, Ethiopia. *Atmosphere*. 2018;9(9). doi.org/10.3390/atmos9090326.
12. Şen Z. Trend Identification Simulation and Application. *Journal of Hydrologic Engineering*. 2014;19(3). doi.org/10.1061/(ASCE)HE.1943-5584.0000811
13. Sanikhani H, Kisi O, Mirabbasi R, Meshram SG. Trend Analysis of Rainfall Pattern over the Central India during 1901–2010. *Arabian Journal of Geosciences*, 2018;11,437. doi.org/10.1007/s12517-018-3800-3.
14. Malik A, Anil Kumar, Guhathakurta P, Kisi O. Spatial-Temporal Trend Analysis of Seasonal and Annual Rainfall (1966–2015) Using Innovative Trend Analysis Method with Significance Test. *Arabian Journal of Geosciences*. 2019;12,328. doi.org/10.1007/s12517-019-4454-5.
15. Wang Y, Xu Y, Tabari H, Wang J, Wang Q, Song S, et al. Innovative Trend Analysis of Annual and Seasonal Rainfall in the Yangtze River Delta, Eastern China. *Atmospheric Research*. 2020;231. doi.org/10.1016/j.atmosres.2019.104673.
16. Kaushika GS, Arora H, Hari Prasad KS. Analysis of climate change effects on crop water availability for paddy,wheat and berseem. *Agricultural Water Management*. 2019;225. doi.org/10.1016/j.agwat.2019.105734
17. Torres M, Howitt R, Rodrigues L. Analyzing rainfall effects on agricultural income: Why timing matters. *Economia*. 2019; 20,1–14. doi.org/10.1016/j.econ.2019.03.006
18. Alam MM, Toriman ME, Siwar C, Talib B. Rainfall Variation and Changing Pattern of Agricultural Cycle: A Study on Paddy Farming in Malaysia. *American Journal of Environmental Sciences*. 2011;7(1),82-89.
19. Pathak H, Pramanik P, Khanna M, Kumar A. Climate change and water availability in Indian agriculture: Impacts and adaptation. *Indian Journal of Agricultural Sciences*. 2014;84(6):671–9.
20. Zachariah M, Mondal A, Das M, AchutaRao KM, Ghosh S. On the role of rainfall deficits and cropping choices in loss of agricultural yield in Marathwada, India. *Environ. Res. Lett*. 2020;15. doi.org/10.1088/1748-9326/ab93fc
21. Alifujiang Y, Abuduwaili J, Maihemuti B, Emin B, Groll M. Innovative Trend Analysis of Precipitation in the Lake Issyk-Kul Basin, Kyrgyzstan. *Atmosphere*. 2020;11,332. doi:10.3390/atmos11040332
22. Güçlü YS. Improved visualization for trend analysis by comparing with classical Mann-Kendall test and ITA. *Journal of Hydrology*. 2020;584. doi.org/10.1016/j.jhydrol.2020.124674

23. Şen Z. Innovative trend significance test and applications. *Theor. Appl. Climatol.* 2017;127,939-947. doi.org/10.1007/s00704-015-1681-x
24. Allen RG, Pereira LS, Raes D, Smith M. Crop evapotranspiration guidelines for computing crop water requirements. FAO Irrigation and Drainage Paper 56. FAO, Rome; 1998.
25. Doorenbos J, Pruitt, WO. Crop Water Requirements. FAO Irrigation and Drainage Paper 24, FAO, Rome; 1977.
26. Brouwer C, Prins K, Heibloem M. "Irrigation Water Management: Irrigation Scheduling," Training Manual No. 4. Food and Agriculture Organization, Rome; 1989.
27. Veena B, Menezes J, D'Souza J, Singh R. Hardy Options Eco-Regional Notes on Climate Change and Semi-Arid Regions. CED, Mumbai, 2011.
28. Sai K, Venkata, Joseph A. Trend Analysis of Rainfall of Pattambi Region, Kerala. *International Journal of Current Microbiology and Applied Sciences.* 2018;7(9), 3274-81. doi.org/10.20546/ijcmas.2018.709.406.
29. Pingale S, Khare D, Jat MK Adamowski JF. Spatial and Temporal Trends of Mean and Extreme Rainfall and Temperature for the 33 Urban Centers of the Arid and Semi-Arid State of Rajasthan, India. *Atmospheric Research.* 2013;138,73–90. doi.org/10.1016/j.atmosres.2013.10.024.
30. Naidu CV, Durgalakshmi K, Muni Krishna K, Ramalingeswara Rao S, Satyanarayana GC, Lakshminarayana P, et al. Is Suer Monsoon Rainfall Decreasing over India in the Global Warming Era? *Journal of Geophysical Research Atmospheres.* 2009;114(24),1–16. doi.org/10.1029/2008JD011288.
31. KSNDMC. Change Scenario in Karnataka: A Detailed Parametric Assessment. 2020.
32. Guhathakurta P, Sanap S, Menon P, Prasad AK, Sable ST, Advani SC. Observed Rainfall Variability and Changes over Karnataka State. 2020; Met Monograph No.: ESSO/IMD/HS/Rainfall Variability/13(2020)/37
33. Adarsh S, Reddy MJ. Trend Analysis of Rainfall in Four Meteorological Subdivisions of Southern India Using Nonparametric Methods and Discrete Wavelet Transforms. *International Journal of Climatology.* 2014;35(6),1107–24. doi.org/10.1002/joc.4042.
34. Kumar V, Jain SK, Singh Y. Analyse Des Tendances Pluviométriques de Long Terme En Inde. *Hydrological Sciences Journal.* 2010; 55(4), 484–496. doi.org/10.1080/02626667.2010.481373.